

# SILKOLENE SUPER 4 RANGE

## Semi-synthetic 4-stroke engine oil for modern motorcycles

### Description

SILKOLENE SUPER 4 grades are semi synthetic 4-stroke engine oils designed for use in both On-Road and Off-Road motorcycles. They protect the engine and transmission with advanced additive chemistry from start-up to full power.

SILKOLENE SUPER 4 grades are blended with a high performance additive system incorporating detergents, dispersants and load carrying agents to give excellent engine cleanliness and minimum component wear. SILKOLENE SUPER 4 uses a balanced formulation to ensure correct operation of oil immersed clutches and other drive line components.

### Application

SILKOLENE SUPER 4 10W-40 and 20W-50 are multigrade 4-Stroke engine oils specifically designed for 4-stroke motorcycle engines On or Off-Road.

### Advantages / Benefits

- A choice of two viscosity grades
- Suitable for use in all 4-stroke motorcycle engines on or off road
- Anti-wear and load carrying agents protect camshafts and bearings and other internal components
- Advanced inhibitors and high quality base fluid minimise internal sludge and varnish deposits
- Balanced frictional characteristics give precise and slip-free clutch operation
- Extreme pressure and lubricity additives ensure quiet and trouble-free gearbox lubrication

### Specifications/Approvals

#### SILKOLENE SUPER 4 10W-40

- JASO MA2
- API SJ / SH/ SG / SF Performance

#### SILKOLENE SUPER 4 20W-50

- JASO MA2
- API SF / SG Performance

### FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley  
Stoke-on-Trent, Staffordshire, ST1 5HU  
Tel: +44 (0)1782 203 700  
Email: [contact-uk@fuchs-oil.com](mailto:contact-uk@fuchs-oil.com)

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

**Typical Data: SILKOLENE SUPER 4 RANGE**

SILKOLENE SUPER 4 .....		10W-40	20W-50	
Characteristics	Unit	Test Method		
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	14.0	18.7	IP71
at 40°C	mm <sup>2</sup> /s	91.7	150.0	
Viscosity Index (VI)		157	140	IP226
SAE Rating		10W-40	20W-50	
Pour point	°C	-33	-25	IP15
Flash Point (Closed Cup)	°C	185	195	IP34

**FUCHS LUBRICANTS (UK) PLC**

New Century Street, Hanley  
Stoke-on-Trent, Staffordshire, ST1 5HU  
Tel: +44 (0)1782 203 700  
Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.